

View Online at <https://aerobasegroup.com/nsn/5930-00-401-7728>

Thread Class:

3a single pressure connection

Thread Length:

0.550 inches single pressure connection

Overall Length:

2.500 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Mounting Method:

Inlet connection

Thread Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+1.00/+2500.00 actuation point pounds per square inch gage and +1.00/+2500.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Stimulus Rating:

247.00 actuation point pounds per square inch gage and 239.00 deactuation point pounds per square inch gage and 8.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0