

View Online at <https://aerobasegroup.com/nsn/5930-00-401-7728>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.550 inches single pressure connection

**Overall Length:**

2.500 inches

**Pressure Switch Type:**

Gage

**Width Across Flats:**

0.750 inches

**Mounting Method:**

Inlet connection

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

3.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+1.00/+2500.00 actuation point pounds per square inch gage and +1.00/+2500.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External deactuation point hex nut and external actuation point hex nut

**Contact Stimulus Rating:**

247.00 actuation point pounds per square inch gage and 239.00 deactuation point pounds per square inch gage and 8.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0