NSN 5930-00-402-1035

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-402-1035 **Thread Class:** 2b single mounting facility **Overall Length:** 5.407 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Shaft Length:** 1.688 inches single actuator **Individual Section Quantity:** 6 **Longest Horizontal Distance Between Mounting Centers:** 2.812 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.812 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 15 each section front **Mounting Method:** Threaded hole single mounting facility and bracket single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 16 single actuator **Shaft Type:** Rectangular/square, threaded hole single actuator **Square Shaft Size:** 0.250 inches single actuator **Terminal Type:**

Tab w/screw

NSN 5930-00-402-1035

Rotary Switch - Page 2 of 2



Breaks before makes each section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0