

View Online at <https://aerobasegroup.com/nsn/5930-00-402-6760>

Thread Class:

2b single pressure connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.875 inches

Overall Height:

4.500 inches

Body Diameter:

3.500 inches

Pressure Switch Type:

Gage

Mounting Facility Circle Radius:

1.500 inches

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Base and threaded stud

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

28 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

10.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

3.00 actuation point inches of water and 2.00 deactuation point inches of water and 1.00 differential point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unef single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0