NSN 5930-00-402-6760

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-402-6760

Inread Class:
2b single pressure connection
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.875 inches
Overall Height:
4.500 inches
Body Diameter:
3.500 inches
Pressure Switch Type:
Gage
Mounting Facility Circle Radius:
1.500 inches
Operating Tempurature Rating:
Between 0.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Base and threaded stud
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
28 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
10.00 pounds per square inch
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Three position circular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:

3.00 actuation point inches of water and 2.00 deactuation point inches of water and 1.00 differential point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

NSN 5930-00-402-6760

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unef single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0