NSN 5930-00-402-6798

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-402-6798

| View Online at https://aerobasegroup.com/nsn/5930-00-402-6798 |
|--|
| Hazardous Locations/environmental Protection: |
| Moisture resistant and salt spray resistant and vibration resistant |
| Overall Height: |
| 0.500 inches |
| Body Height: |
| 0.364 inches |
| Overall Diameter: |
| 0.640 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Operating Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit |
| Mounting Method: |
| Surface |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Increase |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 5.0 amperes resistive load first voltage2.0 amperes resistive load second voltage1.0 amperes resistive load third voltage5.0 amperes |
| resistive load fourth voltage |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Stimulus Rating: |
| 190.00 actuation point degrees fahrenheit and 176.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 30.0 ac at sea level first voltage125.0 ac at sea level second voltage250.0 ac at sea level third voltage30.0 dc at sea level fourth voltage |
| Media For Which Designed: |
| Gas or liquid |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Disc |
| Shelf Life: |

--

N/a

Unit Of Measure:

NSN 5930-00-402-6798

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0