## NSN 5930-00-402-7536

Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-402-7536

Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.094 inches
Actuator Style:
Rectangular
Actuator Height:
0.065 inches
Actuator Width:
0.094 inches
Actuator Free Position Height:
0.375 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
212.0 grams
Actuator Movement:
Between 0.030 pretravel inches and 0.035 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/-

## NSN 5930-00-402-7536

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

