NSN 5930-00-402-9130

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-402-9130

Hazardous Locations/environmental Protection:
Watertight
Overall Height:
4.000 inches
Overall Width:
3.625 inches
Shaft Diameter:
0.500 inches single actuator
Shaft Length:
0.562 inches single actuator
Unthreaded Mounting Hole Diameter:
0.375 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
81487
Longest Horizontal Distance Between Mounting Centers:
5.750 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.750 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section front
Throw Quantity:
1 single section front
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab w/screw

NSN 5930-00-402-9130

Rotary Switch - Page 2 of 2



Contact	Switching	Action
Dua alsa la	-fl	

Breaks before makes single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0