Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-402-9133

| Hazardous Locations/environmental Protection: |
|---|
| Watertight |
| Overall Height: |
| 4.000 inches |
| Overall Width: |
| 3.625 inches |
| Shaft Diameter: |
| 0.500 inches single actuator |
| Shaft Length: |
| 0.562 inches single actuator |
| Unthreaded Mounting Hole Diameter: |
| 0.375 inches single mounting facility |
| Individual Section Quantity: |
| 1 |
| Knob Manufacturer Code: |
| 81487 |
| Longest Horizontal Distance Between Mounting Centers: |
| 5.750 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 1.750 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 single section front |
| Throw Quantity: |
| 1 single section front |
| Mounting Method: |
| Base single mounting facility |
| Features Provided: |
| Actuator knob and metallic inclosure |
| Contact Voltage Rating In Volts: |
| 600.0 highest ac voltage rating at sea level |
| Switch Actuator Momentary Position: |
| Clockwise single actuator |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 2 single actuator |
| Shaft Type: |
| Round single actuator |
| Terminal Type: |
| Tab w/screw |
| |

NSN 5930-00-402-9133

Rotary Switch - Page 2 of 2



Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0