

View Online at <https://aerobasegroup.com/nsn/5930-00-402-9291>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

Between 0.450 inches and 0.490 inches

Body Length:

Between 0.570 inches and 0.575 inches

Body Width:

Between 0.530 inches and 0.535 inches

Body Height:

Between 0.635 inches and 0.640 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.240 inches

Actuator Height:

Between 0.667 inches and 0.707 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0