

View Online at <https://aerobasegroup.com/nsn/5930-00-404-4028>

**Thread Class:**

3b single pressure connection

**Inside Diameter:**

0.438 inches single connection

**Thread Length:**

0.370 inches single pressure connection

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.000 inches

**Overall Height:**

3.620 inches

**Overall Width:**

1.620 inches

**Body Diameter:**

1.500 inches

**Mounting Slot Width:**

0.201 inches

**Unthreaded Mounting Hole Diameter:**

0.201 inches

**Longest Horizontal Distance Between Mounting Centers:**

0.625 inches

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Slot and unthreaded hole

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+2.00/+12.00 actuation point pounds per square inch gage and +1.00/+11.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External deactuation point hex nut and external actuation point hex nut

**Contact Stimulus Rating:**

1.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/lugs

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0