

View Online at <https://aerobasegroup.com/nsn/5930-00-404-4028>

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Thread Length:

0.370 inches single pressure connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.000 inches

Overall Height:

3.620 inches

Overall Width:

1.620 inches

Body Diameter:

1.500 inches

Mounting Slot Width:

0.201 inches

Unthreaded Mounting Hole Diameter:

0.201 inches

Longest Horizontal Distance Between Mounting Centers:

0.625 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Slot and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+2.00/+12.00 actuation point pounds per square inch gage and +1.00/+11.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Stimulus Rating:

1.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0