## NSN 5930-00-404-6107

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-404-6107 **Thread Class:** 2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Corrosion resistant **Overall Length:** 2.406 inches **Overall Height:** 3.562 inches **Overall Width:** 0.750 inches **Body Length:** 2.000 inches **Body Width:** 0.562 inches **Body Height:** 3.562 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.812 inches **Actuator Style:** Round **Actuator Diameter:** 0.312 inches **Actuator Height:** 0.406 inches **Actuator Free Position Height:** 0.687 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Nonpile-up Contact Arrangement:** 

6 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

## **Switch Actuating Force:**

Between 88.0 ounces and 128.0 ounces

## NSN 5930-00-404-6107

Sensitive Switch - Page 2 of 2



Actuator Movement:
--------------------

0.180 pretravel inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

**Thread Series Designator:** 

Unc

**Terminal Type And Quantity:** 

24 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0