

View Online at <https://aerobasegroup.com/nsn/5930-00-405-0567>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.535 inches single pressure connection and 0.565 inches single pressure connection

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.750 inches

**Body Diameter:**

1.437 inches

**Overall Diameter:**

1.875 inches

**Pressure Switch Type:**

Differential

**Width Across Flats:**

Between 0.684 inches and 0.691 inches

**Operating Temperature Rating:**

Between 20.0 degrees fahrenheit and 120.0 degrees fahrenheit

**Mounting Method:**

Inlet connection

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

250.00 pounds per square inch

**Thread Size:**

0.4375 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

4.00 differential point pounds per square inch gage and 6.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiiq:**

A048b0