NSN 5930-00-405-0940

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-405-0940

Thread Class:						
2a all threaded stud						
Thread Length:						
0.250 inches all threaded stud						
Hazardous Locations/environmental Protection:						
Weatherproof						
Overall Height:						
0.656 inches						
Body Height:						
0.309 inches						
Overall Diameter:						
0.426 inches						
Tempurature Sensing Element Type:						
Internal sensor						
Operating Tempurature Rating:						
85.0 degrees celsius and -62.0 degrees celsius						
Mounting Method:						
Threaded stud						
Thready Qty Per Inch (tpi):						
32 all threaded stud						
Contact Action Stimulus:						
Increase						
Thread Size:						
0.138 inches all threaded stud						
Nonpile-up Contact Arrangement:						
1 pole, single throw, normally open, momentary action						
Terminal Type:						
Tab, solder lug						
Contact Load Current Rating:						
3.0 amperes resistive load second voltage						
Contact Adjustability:						
Deactuation point not adjustable and actuation point not adjustable						
Contact Stimulus Rating:						
Contact Climatas Italing.						
185.00 actuation point degrees fahrenheit and 179.00 deactuation point degrees fahrenheit						
185.00 actuation point degrees fahrenheit and 179.00 deactuation point degrees fahrenheit						
185.00 actuation point degrees fahrenheit and 179.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:						
185.00 actuation point degrees fahrenheit and 179.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage						
185.00 actuation point degrees fahrenheit and 179.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz:						
185.00 actuation point degrees fahrenheit and 179.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage						
185.00 actuation point degrees fahrenheit and 179.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed:						

NSN 5930-00-405-0940

Thermostatic Switch - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0