NSN 5930-00-405-3910

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Dustproof

0.375 inches **Body Length:**



View Online at https://aerobasegroup.com/nsn/5930-00-405-3910

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.500 inches
Actuator Style:
Leaf
Actuator Width:
0.160 inches
Actuator Free Position Height:
0.598 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
7.0 ounces
Actuator Movement:
Between 0.218 pretravel inches and 0.030 overtravel inches and 0.030 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 500.000 milliamperes inductive dc
Special Features:
Gold contacts

NSN 5930-00-405-3910

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0