Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-405-4074

Hazardous Locations/environmenta	Il Protection:
Dustproof	
Overall Length:	
4.750 inches	
Overall Height:	
2.904 inches	
Overall Width:	
2.812 inches	
Unthreaded Mounting Hole Diameter	er:
0.221 inches single mounting facility	
Individual Section Quantity:	
1	
Knob Manufacturer Code:	
82121	
Knob Manufacturer Part Number:	
Н	
Longest Horizontal Distance Betwe	en Mounting Centers:
2.000 inches single mounting facility	
Shortest Horizontal Distance Betwee	en Mounting Centers:
1.000 inches single mounting facility	
Longest Vertical Distance Between	Mounting Centers:
2.188 inches single mounting facility	
Operating Tempurature Range:	
-65.0/+85.0 degrees celsius	
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Pole Quantity:	
1 single section rear	
Throw Quantity:	
3 single section rear	
Mounting Method:	
Bracket single mounting facility and un	nthreaded hole single mounting facility
Features Provided:	
Actuator knob	
Contact Voltage Rating In Volts:	
500.0 highest ac voltage rating at sea	level
Mounting Facility Pattern:	
Isosceles triangle single mounting fac	lity
Switch Actuator Indexing Position	Quantity:
8 single actuator	
Terminal Type:	
Tab w/screw	

NSN 5930-00-405-4074

Rotary Switch - Page 2 of 2



Contact Switching Action: Makes before breaks single section rear Switch Actuator Positioning Increment: 45.0 degrees single actuator Switch Actuator Stop Device Type: Fixed-adjustable stops single actuator **Contact Load Current Rating:** 5.0 amperes resistive load highest ac voltage rating at sea level **Special Features:** Incl escutcheon plate **Precious Material And Location:** Contact and terminal surfaces silver **Precious Material:** Silver Style Designator: Tap, circuit selector Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A052b0