NSN 5930-00-405-4076

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-405-4076

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
9.126 inches
Overall Height:
2.904 inches
Overall Width:
2.812 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
8
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
Н
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
4 4th section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Terminal Type:
Tab w/screw

NSN 5930-00-405-4076

Rotary Switch - Page 2 of 2

Fiig: A052b0



Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed-adjustable stops single actuator
Contact Load Current Rating:
5.0 amperes resistive load highest ac voltage rating at sea level
Special Features:
Incl escutcheon plate
Precious Material And Location:
Contact and terminal surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No