## NSN 5930-00-405-7951

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-405-7951 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Body Length:** 1.938 inches **Body Width:** 0.688 inches **Body Height:** 0.813 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches **Actuator Length:** 2.469 inches **Actuator Style:** Leaf **Actuator Width:** 0.188 inches **Actuator Free Position Height:** 1.094 inches **Maximum Voltage Rating In Volts:** 480.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 0.5 ounces **Switch Actuating Force:** Between 1.0 ounces and 2.5 ounces **Actuator Movement:** Between 0.125 pretravel inches and 0.375 pretravel inches and 0.188 overtravel inches and 0.078 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 250.000 milliamperes resistive dc and 20.000 amperes resistive ac **Terminal Type And Quantity:** 3 screw Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5930-00-405-7951

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0