NSN 5930-00-405-8245

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-405-8245

Hole mounted
Overall Length:
0.785 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.968 inches
Overall Width:
0.250 inches
Body Length:
0.785 inches
Body Width:
0.250 inches
Body Height:
0.358 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.781 inches
Actuator Roller Diameter:
0.125 inches
Actuator Roller Width:
0.187 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces

7.0 ounces

Actuator Movement:

Switch Actuating Force:

Between 0.219 pretravel inches and 0.030 overtravel inches and 0.025 differential inches

NSN 5930-00-405-8245

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

One mtg hole elongated to 0.096 in.

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0