

View Online at <https://aerobasegroup.com/nsn/5930-00-406-0278>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

10.750 inches

Overall Height:

2.125 inches

Body Diameter:

5.750 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Distance Between Mounting Facility Centers:

2.000 inches

Capillary Tube Length:

144.0 inches

Bulb Length:

3.000 inches

Bulb Diameter:

0.688 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

220.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case and tubing end seal connection

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+100.00/+200.00 actuation point degrees fahrenheit and +100.00/+200.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob and external deactuation point knob

Contact Voltage Rating In Volts:

230.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A048b0