

View Online at <https://aerobasegroup.com/nsn/5930-00-406-6239>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

Between 1.740 inches and 1.780 inches

Overall Height:

Between 1.625 inches and 1.645 inches

Overall Width:

Between 1.140 inches and 1.160 inches

Unthreaded Mounting Hole Diameter:

0.090 inches single mounting facility and 0.110 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.570 inches single mounting facility and 1.610 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.890 inches single mounting facility and 0.910 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

A7 fms aircraft

Mounting Method:

Flange single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

Contact Arrangement Truth Table:

Bcd, 1 pole - 10 positions each section

Color:

White each indicator marking

Precious Material And Location:

Printed circuit board surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0