

View Online at <https://aerobasegroup.com/nsn/5930-00-406-6239>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

Between 1.740 inches and 1.780 inches

**Overall Height:**

Between 1.625 inches and 1.645 inches

**Overall Width:**

Between 1.140 inches and 1.160 inches

**Unthreaded Mounting Hole Diameter:**

0.090 inches single mounting facility and 0.110 inches single mounting facility

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.570 inches single mounting facility and 1.610 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.890 inches single mounting facility and 0.910 inches single mounting facility

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**End Application:**

A7 fms aircraft

**Mounting Method:**

Flange single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel all actuators

**Features Provided:**

Metallic inclosure

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

10 all actuators

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

**Contact Arrangement Truth Table:**

Bcd, 1 pole - 10 positions each section

**Color:**

White each indicator marking

**Precious Material And Location:**

Printed circuit board surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0