NSN 5930-00-407-0660

Push-pull Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-407-0660 **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Flame resistant **Overall Height:** 1.391 inches **Overall Width:** 1.391 inches **Body Diameter:** 0.562 inches **Bushing Length:** 0.312 inches **Body Length:** 0.782 inches **Actuator Diameter:** 0.375 inches **Actuator Height:** 0.375 inches **Actuator Color:** Red single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 1 pole, single throw, double make, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac **Special Features:** Styl dimensions do not include assembled accessories specified in army dwg no. 10233568 **Thread Series Designator:** Unef **Terminal Type And Quantity:**

N/a

2 tab, solder lug

Unit Of Measure:

Shelf Life:

NSN 5930-00-407-0660Push-pull Switch - Page 2 of 2



em			

No

Fiig:

A053a0