

View Online at <https://aerobasegroup.com/nsn/5930-00-407-1589>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Waterproof

**Overall Length:**

2.100 inches

**Overall Height:**

Between 0.615 inches and 0.650 inches

**Overall Width:**

Between 0.615 inches and 0.650 inches

**Body Diameter:**

Between 0.615 inches and 0.650 inches

**Bushing Length:**

0.420 inches

**Body Length:**

1.290 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.500 amperes inductive dc and 500.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 500.000 milliamperes lamp ac

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 tab, solder lug

**Specification Data:**

81349-mil-s-22885/18 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0