

View Online at <https://aerobasegroup.com/nsn/5930-00-407-1589>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

2.100 inches

Overall Height:

Between 0.615 inches and 0.650 inches

Overall Width:

Between 0.615 inches and 0.650 inches

Body Diameter:

Between 0.615 inches and 0.650 inches

Bushing Length:

0.420 inches

Body Length:

1.290 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.500 amperes inductive dc and 500.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 500.000 milliamperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 tab, solder lug

Specification Data:

81349-mil-s-22885/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0