

View Online at <https://aerobasegroup.com/nsn/5930-00-407-1936>

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.938 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

1.250 inches

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 8: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

2 single section front

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.344 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0