NSN 5930-00-407-1978

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-407-1978

| Hazardous Locations/environmental Protection: |
|---------------------------------------------------|
| Explosion proof |
| Overall Diameter: |
| Between 0.540 inches and 0.560 inches |
| Individual Section Quantity: |
| 1 |
| Knob Manufacturer Code: |
| 02111 |
| Operating Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 single section rear |
| Throw Quantity: |
| 10 single section rear |
| Mounting Method: |
| Printed circuit single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 10 single actuator |
| Terminal Type: |
| Printed circuit |
| Contact Switching Action: |
| Breaks before makes single section rear |
| Switch Actuator Positioning Increment: |
| 36.0 degrees single actuator |
| Contact Load Current Rating: |
| 250.0 milliamperes resistive load dc at sea level |
| Style Designator: |
| Miniature, pin mount |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A052b0