

View Online at <https://aerobasegroup.com/nsn/5930-00-407-2704>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.625 inches single mounting facility

**Width Between Flats:**

0.187 inches single actuator

**Overall Length:**

8.344 inches

**Overall Height:**

2.812 inches

**Overall Width:**

2.000 inches

**First Flat Length:**

0.265 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.960 inches single actuator

**Individual Section Quantity:**

4

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 each section front

**Throw Quantity:**

3 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

110.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, parallel flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

40.0 degrees single actuator

**Contact Load Current Rating:**

9.0 amperes resistive load ac at sea level

**Special Features:**

Six dummy terminals on the front of all sections

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0