

View Online at <https://aerobasegroup.com/nsn/5930-00-407-2704>

Thread Class:

2a single mounting facility

Thread Length:

0.625 inches single mounting facility

Width Between Flats:

0.187 inches single actuator

Overall Length:

8.344 inches

Overall Height:

2.812 inches

Overall Width:

2.000 inches

First Flat Length:

0.265 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.960 inches single actuator

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section front

Throw Quantity:

3 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

110.0 ac at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

40.0 degrees single actuator

Contact Load Current Rating:

9.0 amperes resistive load ac at sea level

Special Features:

Six dummy terminals on the front of all sections

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0