

View Online at <https://aerobasegroup.com/nsn/5930-00-407-6377>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.530 inches

Body Width:

0.200 inches

Body Height:

0.360 inches

Unthreaded Mounting Hole Diameter:

0.095 inches

Actuator Length:

0.528 inches

Actuator Style:

Leaf

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.330 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

4.0 ounces

Actuator Movement:

Between 0.090 pretravel inches and 0.045 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0