NSN 5930-00-407-6794

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-407-6794

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
5.376 inches
Overall Height:
2.906 inches
Overall Width:
2.813 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
Н
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
6 each section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

Makes before breaks each section rear

NSN 5930-00-407-6794

Rotary Switch - Page 2 of 2

Fiig: A052b0



Switch Actuator Positioning Increment: 45.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed-adjustable stops single actuator **Contact Load Current Rating:** 5.0 amperes resistive load highest ac voltage rating at sea level **Special Features:** Incl escutcheon plate **Precious Material And Location:** Contact and terminal surfaces silver **Precious Material:** Silver Style Designator: Tap, circuit selector Shelf Life: N/a **Unit Of Measure: Demilitarization:** No