## NSN 5930-00-408-2279

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-408-2279

**Thread Class:** 

2a single mounting facility

Thread Length:

0.313 inches single mounting facility

**Overall Length:** 

2.126 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.500 inches single actuator

**Overall Diameter:** 

1.000 inches

**Nonturn Device Radius:** 

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

**Throw Quantity:** 

9 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

9 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

## **NSN 5930-00-408-2279**Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load ac at sea level
Precious Material And Location:
Rotor blades and contacts silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
- <del>-</del>
Demilitarization:
No
Fiig:
A052b0