

View Online at <https://aerobasegroup.com/nsn/5930-00-408-8749>

Thread Class:

2a single mounting facility

Thread Length:

0.218 inches single mounting facility

Width Between Flats:

0.063 inches single actuator and 0.064 inches single actuator

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.731 inches

First Flat Length:

0.121 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.313 inches single actuator

Overall Diameter:

0.710 inches

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

10 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, parallel flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+20.000/+30.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0