

View Online at <https://aerobasegroup.com/nsn/5930-00-408-8750>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.218 inches single mounting facility

**Width Between Flats:**

0.063 inches single actuator and 0.064 inches single actuator

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

1.571 inches

**First Flat Length:**

0.121 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.313 inches single actuator

**Overall Diameter:**

0.710 inches

**Individual Section Quantity:**

4

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

10 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, parallel flattened single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0