## NSN 5930-00-409-0312

Flow Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-00-409-0312
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
7.375 inches
Overall Height:
6.500 inches
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit
Mounting Method:
Line and threaded bushing
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
14 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.500 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
45.4 milliamperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable, preset
Contact Adjustment Range:
+3.00/+100.00 actuation point gallons per minute
Contact Adjustment Type:
External actuation point hex nut
Contact Stimulus Rating:
75.00 actuation point gallons per minute
Contact Voltage Rating In Volts:
32.0 dc at sea level second voltage
Media For Which Designed:
Liquid
Thread Series Designator:
Npt single threaded bushing
Shelf Life:
N/a
Unit Of Measure:

## NSN 5930-00-409-0312

Flow Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A048b0