

View Online at <https://aerobasegroup.com/nsn/5930-00-409-0785>

Thread Class:

2a single mounting facility

Thread Length:

0.560 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.655 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

1.780 inches

Nonturn Device Radius:

0.610 inches at 3: 00 o'clock and 0.640 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Cam actuated

Thread Size:

0.500 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, single throw, both positions maintained single switch single section rear

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Connector, plug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

40.0 amperes resistive load dc at sea level and 20.0 amperes inductive load dc at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0