

View Online at <https://aerobasegroup.com/nsn/5930-00-409-1595>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.235 inches single mounting facility and 0.265 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 1.696 inches and 1.728 inches

**First Flat Length:**

0.470 inches single actuator and 0.530 inches single actuator

**Flat Height:**

0.088 inches single actuator and 0.098 inches single actuator

**Shaft Diameter:**

0.123 inches single actuator and 0.126 inches single actuator

**Shaft Length:**

0.985 inches single actuator and 1.015 inches single actuator

**Overall Diameter:**

Between 0.495 inches and 0.515 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0