NSN 5930-00-409-2212

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-409-2212

Hazardous Locations/environmental Protection:				
Explosion proof				
Overall Length:				
4.657 inches				
Overall Height:				
2.906 inches				
Overall Width:				
2.813 inches				
Individual Section Quantity:				
1				
Knob Manufacturer Code:				
82121				
Longest Horizontal Distance Between Mounting Centers:				
2.000 inches single mounting facility				
Shortest Horizontal Distance Between Mounting Centers:				
1.000 inches single mounting facility				
Longest Vertical Distance Between Mounting Centers:				
2.188 inches single mounting facility				
Switch Contact Basic Design:				
Nonpile-up symmetrical				
Pole Quantity:				
2 single section front				
Throw Quantity:				
1 single section front				
Features Provided:				
Actuator knob				
Contact Voltage Rating In Volts:				
600.0 ac at sea level				
Switch Actuator Momentary Position:				
Clockwise single actuator				
Mounting Facility Pattern:				
Isosceles triangle single mounting facility				
Switch Actuator Indexing Position Quantity:				
2 single actuator				
Terminal Type:				
Tab w/screw				
Contact Switching Action:				
Breaks before makes single section front				
Switch Actuator Positioning Increment:				
45.0 degrees single actuator				
Switch Actuator Stop Device Type:				

Fixed stop single actuator

NSN 5930-00-409-2212

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

20.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0