# NSN 5930-00-409-2306

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-409-2306

## **Thread Class:**

2b single mounting facility

## **Overall Length:**

5.063 inches

# **Overall Height:**

2.188 inches

#### **Overall Width:**

2.188 inches

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

1.937 inches single actuator

## **Distance Between Mounting Facility Centers:**

1.500 inches single mounting facility

## **Individual Section Quantity:**

3

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

4 3rd section rear

## Throw Quantity:

4 3rd section rear

# Mounting Method:

Threaded hole single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.164 inches single mounting facility

## **Contact Voltage Rating In Volts:**

115.0 dc at sea level

## **Mounting Facility Pattern:**

Two position in-line single mounting facility

## Switch Actuator Indexing Position Quantity:

4 single actuator

## Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes 2nd section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-409-2306

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level

# **Precious Material And Location:**

Contacts and rotor blades silver and terminal surfaces gold

## Precious Material:

Silver and gold

## Style Designator:

Tap, square frame

#### Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A052b0