

View Online at <https://aerobasegroup.com/nsn/5930-00-409-2990>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.497 inches and 0.503 inches

Body Length:

Between 0.771 inches and 0.796 inches

Body Width:

Between 0.245 inches and 0.265 inches

Body Height:

Between 0.756 inches and 0.771 inches

Unthreaded Mounting Hole Diameter:

Between 0.088 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.120 inches and 0.130 inches

Actuator Height:

0.100 inches

Actuator Free Position Height:

Between 0.386 inches and 0.406 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 8.0 ounces and 16.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 8.000 amperes resistive ac

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0