

View Online at <https://aerobasegroup.com/nsn/5930-00-409-3485>

Thread Class:

2a all threaded stud

Thread Length:

1.000 inches all threaded stud

Overall Length:

5.000 inches

Outside Diameter:

0.500 inches single connection

Overall Height:

9.000 inches

Overall Width:

4.625 inches

Distance Between Mounting Facility Centers:

2.250 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -10.0 degrees celsius and 55.0 degrees celsius

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.15/+2.00 actuation point inches of water and +0.15/+2.00 deactuation point inches of water

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

0.65 actuation point inches of water and 0.55 deactuation point inches of water and 0.10 differential point inches of water

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

External seat-gasket seal, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0