

View Online at <https://aerobasegroup.com/nsn/5930-00-409-3500>

**Thread Class:**

2a single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

4.781 inches

**Overall Height:**

2.500 inches

**Overall Width:**

2.406 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.125 inches single actuator

**Individual Section Quantity:**

8

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

101605a-2a

**Longest Horizontal Distance Between Mounting Centers:**

1.641 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.641 inches single mounting facility

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

4 each section front

**Mounting Method:**

Threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0