

View Online at <https://aerobasegroup.com/nsn/5930-00-409-9350>

**Thread Class:**

2b 1st mounting facility

**Thread Length:**

0.375 inches 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Rainproof

**Overall Length:**

2.880 inches

**Overall Height:**

2.500 inches

**Overall Width:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.201 inches single mounting facility

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.640 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.640 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

1.155 inches 1st mounting facility

**Mounting Method:**

Threaded bushing 2nd mounting facility

**Features Provided:**

Actuator knob and dummy section

**Thready Qty Per Inch (tpi):**

32 2nd mounting facility

**Thread Size:**

0.469 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

120.0 dc at sea level

**Mounting Facility Pattern:**

Four position circular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Uns 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0