

View Online at <https://aerobasegroup.com/nsn/5930-00-409-9350>

Thread Class:

2b 1st mounting facility

Thread Length:

0.375 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Rainproof

Overall Length:

2.880 inches

Overall Height:

2.500 inches

Overall Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.201 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.640 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.640 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.155 inches 1st mounting facility

Mounting Method:

Threaded bushing 2nd mounting facility

Features Provided:

Actuator knob and dummy section

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.469 inches 2nd mounting facility

Contact Voltage Rating In Volts:

120.0 dc at sea level

Mounting Facility Pattern:

Four position circular 1st mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Uns 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0