NSN 5930-00-410-1723

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-410-1723

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Actuator Length:

3.500 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

1.500 inches

Actuator Roller Width:

0.312 inches

Housing Height:

3.062 inches

Housing Length:

9.250 inches

Housing Width:

3.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

8.625 inches

Maximum Voltage Rating In Volts:

440.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Actuator Movement:

40.0 pretravel degrees and 15.0 overtravel degrees

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 1.500 amperes resistive ac

Special Features:

Cw and ccw operation

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

NSN 5930-00-410-1723

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

