

View Online at <https://aerobasegroup.com/nsn/5930-00-410-7519>

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.410 inches

First Flat Length:

0.310 inches single actuator

Shaft Diameter:

0.190 inches single actuator

Shaft Length:

0.380 inches single actuator

Overall Diameter:

Between 0.620 inches and 0.660 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 12: 00 o'clock

Operating Temperature Range:

+40.0/+115.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

6 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.312 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Shaft Flat/slot Angular Location:

300.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0