

View Online at <https://aerobasegroup.com/nsn/5930-00-411-2076>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

6.750 inches

Overall Width:

4.380 inches

First Flat Length:

0.880 inches single actuator

Flat Height:

0.250 inches single actuator

Shaft Diameter:

0.380 inches single actuator

Shaft Length:

1.130 inches single actuator

Unthreaded Mounting Hole Diameter:

0.312 inches 2nd mounting facility and 0.317 inches 2nd mounting facility

Individual Section Quantity:

16

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

A

Knob Specification Markings:

Indicating arrow

Longest Horizontal Distance Between Mounting Centers:

2.281 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.281 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

240.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0