NSN 5930-00-411-8747

amperes inductive ac and 2.000 amperes lamp ac

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-411-8747

Body Style:
Bushing mount
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.346 inches
Overall Height:
2.770 inches
Overall Width:
1.025 inches
Bushing Length:
0.470 inches
Body Length:
1.346 inches
Body Width:
1.025 inches
Actuator Style:
Round
Actuator Diameter:
0.430 inches
Actuator Height:
1.050 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
1.250 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, three positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

18.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 11.000 amperes resistive ac and 8.000

NSN 5930-00-411-8747 Toggle Switch - Page 2 of 2



Inread Series Designator:
Uns
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0