

View Online at <https://aerobasegroup.com/nsn/5930-00-412-1071>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Shaft Diameter:**

0.500 inches single actuator

**Shaft Length:**

0.750 inches single actuator

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded hole single mounting facility

**Features Provided:**

Metallic inclosure

**Thready Qty Per Inch (tpi):**

18 single mounting facility

**Thread Size:**

0.312 inches single mounting facility

**Contact Voltage Rating In Volts:**

575.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, fluted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

68.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:**

10 degrees lever travel to trip switch, two 1/2-14 thd @conduit entrances on top

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0